

[Home](#) ■ [Solutions](#) ■ [Sludge Treatment](#) ■ [Sludge Disinfection](#)

HUBER Solutions for Sludge Disinfection

According to the German Fertilizer Regulation only sewage sludge that is hygienically safe for human and plant health is still allowed for agricultural use. Similar regulations can also be found in many other countries today.

Pathogens can be inactivated through disinfection (also called hygienisation).

In thermal processes the sludge is heated to a minimum temperature for a minimum period. When liquid sewage sludge is pre-pasteurized (e. g. for 30 minutes at 70 °C) before it is digested, heat is recovered with the use of sludge / sludge-heat exchangers. To prevent clogging of the heat exchangers the sludge must be screened, for example in our [Strainpress@ Sludgecleaner SP](#).

Our middle-temperature [HUBER Belt Dryer BT](#) achieves that the sewage sludge is not only dried but also disinfected if the sludge is warmer than 70 °C for longer than 30 minutes.

In [Solar Dryers](#) continuous disinfection is not always possible due to the moderate temperature. The dried sludge is however disinfected if stored in a glasshouse for a year or or when fully dried and kept in summery environmental conditions.

Huber Technology Middle East (FZE)
P.O. Box: 120137
Plot J2-08
Sharjah International Free Zone
United Arab Emirates

Tel.: +971 6 5574059
Fax: +971 6 5574069

Email: info@huberme.com
Internet: www.huberme.com

Member of the HUBER group:
www.huber.de